

Siplast Primer

Quick-drying solvent based elastomeric bitumen primer



- ▶ Quick drying time
- ▶ Universal
- ▶ Application on all types of substrates and decks, in buildings and civil engineering (bridgedeck waterproofing)
- ▶ Suitable for all types of bituminous Siplast systems (torched, self-adhesive, bonded with hot bitumen)

Packaging

- Cans of 2l, 10l or 25l

Main uses

- Cold-applied, universal elastomeric bitumen primer for application on all types of substrates and metal or wooden decks.
- To be used under all types of bituminous Siplast membranes (torched, self-adhesive, bonded with hot bitumen) .

Description

- Elastomeric bitumen, Xylene solvent.

Performances

- Drying time (at 23°C): 2h.
- Flash point: 25°C; contains solvents (flammable product).

Application

Siplast Primer : universal, cold-applied bituminous primer with quick drying time. Apply by brush, roller or spraying devices.

Customs nomenclature

27 15 00 00 000 1T

Safety

Siplast Primer is rated as flammable and noxious (F et Xn) according to the European Directives and fitted with labelling and packaging for dangerous substances (1999/45/CE).

This product is provided with a Safety Data Sheet issued by Siplast, website: www.siplast-international.com/MSDS.asp

The persons handling and applying this product need to have it in their possession in order to be informed of hazards and aid measures.

This document is only a guide. Siplast-Icopal reserves the right to change the composition and fixing recommendations of products as a result of evolution of knowledge and technology.



12, rue de la Renaissance
F-92184 Antony Cedex
Tél. +33 (0)1 40 96 35 00
Fax. +33 (0)1 46 66 24 85
www.siplast-international.com

ISO 9001
BUREAU VERITAS
Certification



L'ensemble des sites de la Société