

**PRODUCT TECHNICAL INFORMATION**  
ITA/ATEXP/475  
Rev. 1 – 15/07/10

# PARATHANE MAT

## POLYAMIDE FABRIC

### CLASSIFICATION:

Polyamide fabric (Nylon jersey)

### SCOPE OF APPLICATION:

Reinforcement of all details as angles, cracks and gaps.

### TECHNICAL CHARACTERISTICS:

- Weight:  $\geq 70 \text{ g/m}^2$
- Tensile strength (MD) : 66N/cm
- Elongation at break (MD) : 75%



### APPLICATION:

PARATHANE MAT is applied between two coats of PARATHANE COATING

### APPLICATION CONDITIONS:

Minimum temperature:  $> 5^{\circ}\text{C}$

Maximum temperature:  $< 40^{\circ}\text{C}$

Relative Humidity:  $< 90\%$

The surface of the substrate should be dry and at least  $+3^{\circ}\text{C}$  above the dew point.

### DRYING CONDITIONS :

See drying conditions of the top coat



## **PACKAGING/STORAGE :**

**PARATHANE MAT** is supplied in 0,15 x 50 m rolls

Rolls should be stored in dry environment.

Protect the product against moisture, direct sunlight and extremes of temperature.

Storage temperature: 5°C to 35°C.

## **HEALTH & SAFETY:**

**PARATHANE MAT** is not an hazardous material

Our technical advice-whether verbal, written or by way of trials- is given in good faith, but without warranty, and this also applies where proprietary rights of third parties are involved. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended processes and uses. The application, use and processing of the products are beyond our control and therefore, entirely your own responsibility. Should, in spite of this, liability be established for any damage that occurred due to defective material, it will be limited to the value of the goods used by you at this point of damage. We will, of course, provide products of consistent quality within the scope of our General Conditions of Sale and Delivery.