

FONDAPLY2

DEFINITION

FONDAFOR is a SBS self adhesive bituminous membrane for damp proof courses.



SCOPE OF APPLICATION

Membrane for a single layer waterproofing system of underground walls.

Applied upon : Waterproofing of buried walls.
Applied by : Self adhesive.

DESCRIPTION

Surface	Synthetic film
Blend	Adhesive bitumen
Reinforcement	Synthetic film
Under face	Peelable film

DIMENSIONAL CHARACTERISTICS

	Nominal value	Critical value
Thickness at the selvedge (mm)	1.5	1.4
Length (m)	20	19.80
Width (m)	1	0.99
Weight of a roll (kg)	29.7	29.1
Weight/m ² (kg)	1.47	1.39

PERFORMANCES

	Norm	Unit	Nominal values	Critical values
Tensile strength	EN 12311-1	N/5cm	170 x 170	170 x 170
Elongation	EN 12311-1	%	18 x 18	18 x 18
Nail tearing resistance	EN 12310-1	N	85 x 85	85 x 85
Cold bending resistance	EN 1109	°C	-15	-15
Static puncturing resistance	EN 12730	kg	20	

PACKAGING

FONDAFOR	Rolls/truck pallet	Rolls/container pallet	Rolls/wooden box
	20	25	